

## Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/Actuator cable, 3-position, PVC, Black RAL 9005, Free cable end, on Socket straight M8, Cable length: 10 m



### Key commercial data

|                        |   |
|------------------------|---|
| Packing unit           | 0   |
| Minimum order quantity | 1   |
| GTIN                   | <br>4 046356 724838 |
| Custom tariff number   | 85444290  |
| Country of origin      | POLAND  |

### Technical data

#### General data

|                                 |  |
|---------------------------------|--|
| Rated current at 40°C           | 4 A  |
| Rated voltage                   | 60 V   |
| Number of positions             | 3  |
| Volume resistance               | ≤ 5 mΩ   |
| Insulation resistance           | ≥ 100 MΩ   |
| Length of cable                 | 10 m   |
| Ambient temperature (operation) | -25 °C ... 90 °C (Male connector / female connector) |

#### General characteristics

|                          |   |
|--------------------------|---|
| Standards/regulations    | M8 plug-in connector IEC 61076-2-104        |
| Coding                   | A - standard                                |
| Degree of protection     | IP65/67                                     |
| Torque                   | 0.2 Nm (M8 plug-in connectors)              |
| Contact material         | CuSn  |
| Contact surface material | Ni/Au                                       |
| Contact carrier material | TPU GF                                      |
| Material of grip body    | TPU, hardly inflammable, self-extinguishing |
| Material, knurls         | Zinc die-cast, nickel-plated                |
| Status display           | No  |

## Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

### Technical data

#### Conductor data

|                                    |  |
|------------------------------------|--|
| Cable type                         | PVC black                                      |
| Cable type (abbreviation)          | PVC  |
| Cable abbreviation                 | LiYY   |
| Conductor cross section            | 3x 0.25 mm <sup>2</sup> (signal line)          |
| AWG signal line                    | 24   |
| Conductor structure signal line    | 32x 0.10 mm                                    |
| Core diameter including insulation | 1.32 mm ±0.02 mm                               |
| Thickness, insulation              | ≥ 0.23 mm (Core insulation)                    |
| Thickness, insulation              | ≥ 0.76 mm (Outer cable sheath)                 |
| Wire colors                        | brown, blue, black                             |
| Overall twist                      | 3 wires, twisted                               |
| External sheath, color             | Black RAL 9005                                 |
| External cable diameter D          | 4.4 mm ±0.15 mm                                |
| Cable weight                       | 29 kg/km                                       |
| Outer sheath, material             | PVC  |
| Material conductor insulation      | PVC  |
| Conductor material                 | Bare Cu litz wires                             |
| Insulation resistance              | ≥ 100 MΩ*km (at 20 °C)                         |
| Conductor resistance               | max. 78 Ω/km (at 20 °C)                        |
| Nominal voltage, conductor         | ≥ 300 V  |
| Test voltage, conductor            | ≤ 3000 V                                       |
| Flame resistance                   | As per UL-Style 2464                           |
| Ambient temperature (operation)    | -25 °C ... 80 °C (cable, fixed installation)   |
| Ambient temperature (operation)    | -5 °C ... 80 °C (cable, flexible installation) |

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |

# Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |

## Approvals

### Approvals


#### Approvals


UL Listed / cUL Listed / cULus Listed

#### Ex Approvals

#### Approvals submitted

## Approval details

|   |       |
|---|-------|
| UL Listed  |       |
| Nominal current I <sub>N</sub>  | 4 A   |
| Nominal voltage U <sub>N</sub>  | 125 V |

|  |       |
|--|-------|
| cUL Listed  |       |
| Nominal current I <sub>N</sub>   | 4 A   |
| Nominal voltage U <sub>N</sub>   | 125 V |

|  |  |
|--|--|
| cULus Listed  |  |
|--|--|

## Accessories

### Accessories

### Marking

## Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

### Accessories

Insert label - PABA WH/15 - 1013151



Insert label, white, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

---

Insert label - PABA YE/15 - 1013698



Insert label, yellow, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

---

Insert label - PABA RD/15 - 1013944



Insert label, red, Unlabeled, Can be labeled with: Plotter, Mounting type: Thread on, Cable diameter: 0.6-50 mm, Lettering field: 15 x 4 mm

---

Conductor marker carrier - PATG 2/23 - 1013850



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 2-4 mm, Lettering field: 4 x 23 mm

---

Conductor marker carrier - PATG 3/23 - 1013863



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 4-7 mm, Lettering field: 4 x 23 mm

---

Conductor marker carrier - PATG 4/23 - 0808011



Conductor marker carrier, transparent, Unlabeled, Mounting type: Slide on, Cable diameter: 6-10 mm, Lettering field: 4 x 23 mm

## Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

### Accessories

---

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

---

### Protection and sealing elements

Screw plug - PROT-M 8 MS-PA-CHAIN - 1430860

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 sockets



### Tools

Cable-cutting tool - CUTFOX-S VDE - 1212207



Diagonal cutter for copper and aluminum conductors, VDE-tested

---

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from  $\varnothing$  of 4.4 to 7 mm, any stripping length

---

Stripping tool - WIREFOX 10 - 1212150



Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

---

# Sensor/Actuator cable - SAC-3P-10,0-PVC/M 8FS B-L - 1404700

## Accessories

Torque screwdriver - TSD 02 SAC - 1208487



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors


Tool - SAC BIT M8-D10 - 1208461



Nut for assembling sensor/actuator cables with M8 connector and for M8 connectors with QUICKON fast connection technology, for 4 mm hexagonal drive


## Drawings

Schematic diagram




Pin assignment M8 socket, 3-pos., view female side

Cable cross section




PVC black [PVC]

Dimensioned drawing



Socket M8 x 1, straight

Circuit diagram



Contact assignment of M8 socket